Przedsiębiorstwo Usługowo Remontowe
REMODEX
Zakład Badań i Wdrożeń Przemysłu Meblarskiego Sp. z o.o.
LABORATORIUM BADAWCZE
Gruszczyn, ul. Leśna 12
62-006 Kobylnica
Email: biuro@remodex.com.pl
KRS 0000099068
tel. kom. +48 601 391 825

Order No	37/26	*Order date:*	09.02.2026
Name and address of the customer	F.H.U. PINEWOOD S.C. K. Kiepura, J. Kiepura Company Registration Number: 5521713774 ul. Spółdzielcza 1 JORDANÓW 34-240 Małopolskie PL Tel. +48733669367		
Product (name, type, symbol, producer)	**Children's cot LUMI 120x60 with guard rail - converts to a toddler bed** EAN: 5900354950103 | SKU: N_LUMI 120x60-BARIERKA-BIALY/NATURA EAN: 5900354950110 | SKU: N_LUMI 120x60-SZUF-BARIERKA-BIALY/NATURA EAN: 5900354950530 | SKU: N_LUMI 120x60-SZUF-BAR+MP-BIALY/NATURA EAN: 5904276316115 | SKU: N_LUMI 120x60-BARIERKA-MIETA EAN: 5904276316139 | SKU: N_LUMI 120x60-SZUF-BAR-MIETA EAN: 5904276316153 | SKU: N_LUMI 120x60-SZUF-BAR-MP-MIETA EAN: 5904276316108 | SKU: N_LUMI 120x60-BARIERKA-KASZMIR EAN: 5904276316122 | SKU: N_LUMI 120x60-SZUF-BAR-KASZMIR EAN: 5904276316146 | SKU: N_LUMI 120x60-SZUF-BAR-MP-KASZMIR		
Product description	**Ends – pine wood frame, rails 45 x 21 mm**, pine wood **slats 20 x 12 mm** Sides – longitudinal **rails of pine wood 35 x 21 mm, pine wood** slats **20 x 12 mm, three** removable rungs **Ø 16 mm. Cot base** – longitudinal **rails** made **of 45 x 18 mm** hardwood plywood, **and bottom** slats **made of 51- 52 x 8 mm** hardwood **plywood.** **The cot can** optionally **have a drawer.**		
Type and scope of tests	strength, durability, stability, **other** requirements according **to standards.**		
Test methods (numbers and titles of standards)	**PN-EN 716-1+AC:2019** Furniture. Children's **cots and folding cots for domestic use – Part 1: Safety** requirements **PN-EN 716-2:2017 Furniture. Children's cots and** folding **cots for domestic use – Part 2: Test** methods		
Date of receipt of samples	**09.02.2026**	*Date of completion of tests*	02.03.2026
Document identifying the product	assembly and use instruction		
Test result	POSITIVE		
The test results are only valid for the article tested. ***This TEST REPORT shall not be reproduced, except in full, without the written approval of the laboratory.***			
Comments:			

Test operator

/M.Sc.(Eng.) Piotr Błaszczak/

Przedsiębiorstwo Usługowo-Remontowe
REMODEX, ZAKŁAD BADAŃ I WDROŻEŃ
PRZEMYSŁU MEBLARSKIEGO Sp. z o.o.
Gruszczyn, ul. Leśna 12
62-006 Kobylnica, tel./fax: 817 49 97
NIP 782-00-23-618 REGON 008058795

Authorised:

M.Sc.(Eng.). Piotr Błaszczak

TESTS according to PN-EN 716-1, PN-EN 716-2

Test sample: **Children's cot LUMI 120 x 60 with guard rail - converts to a toddler bed**

Point of the standard		Test type	Test parameters, Requirements	Test result
PN-EN 716-1	PN-EN 716-2			
4.2.1	---	Materials and surfaces	---	not tested
4.2.2	---	Flammability of textiles, coated textiles and plastics covering	---	not applicable
---	5.1	Assembly and inspection	acc. norm	pass
4.3	5.2	Initial stability	Q=10 kg, P=30 N	pass
4.4.1.1	---	Edges and protruding parts	rounded or chamfered	pass
4.4.1.2	---	Self-tapping screws	inadmissible	pass
4.4.1.3		Labels and decals	acc. norm	pass
4.4.1.4	5.5	Small parts	acc. norm	pass
4.4.1.5	---	Castors and wheels	two castors/wheels can be locked or two other support point	not applicable
4.4.2.1	5.4.1	Holes, gaps and openings inside the cot - general	< 7 mm, from 12 to 25 mm from 45 to 65 mm	pass
4.4.2.2		Assembly holes	inadmissible from 7 to 12 mm deeper than 10 mm	pass
4.4.2.3	5.4.1	Distance between cot base and sides and ends	cone Ø 25 mm P=30 N	pass
4.4.2.4	5.4.1	Openings in mesh sides and ends	cone Ø 7 mm P=30 N	not applicable
4.4.2.5	5.4.1	Distance between slats of the cot base	cone Ø 60 mm P=30 N	pass
4.4.2.6	5.4.1	Openings in mesh of the cot base	cone Ø 85 mm P=90 N	not applicable
4.4.3	5.4.2	Head entrapment on the outside of the cot	small head probe large head probe V and irregular shaped openings template	pass
4.4.4.1	---	Shear and squeeze points when setting up and folding	acc. norm	not applicable
4.4.4.2	---	Shear and squeeze points under the influence of powered mechanisms	acc. norm	not applicable
4.4.4.3	---	Shear and squeeze points during use	acc. norm	pass

Point of the standard		Test type		Test parameters. Requirements	Test result
PN-EN 716-1	PN-EN 716-2				
4.4.5	5.10	Snag points		**ball chain with mass 2,5 kg**	pass
4.4.6.1 4.4.6.2	5.11	Locking systems **for** folding **cots all locking systems**		acc. norm	pass*/
4.4.7.1.	5.7.1	**Folding mattress base and cot base**		acc. norm	not applicable
4.4.7.2	5.3	**Adjustable cot base**		acc. norm	pass
4.4.7.3	5.7.2	Strength of the cot base		**Q=10 kg, h=150 mm 1000 x at any point**	pass
4.4.8.1	---	Movable sides		acc. norm	not applicable
4.4.8.2	5.9.1	**Distance between footholds and top of cot sides and ends**	**cot base in the bottom position**	P=300 N, min 500 mm	**650 mm pass**
	5.3.3		footholds	min. 500 mm	**610 mm pass**
	---		**cot base in the upper position**	**min, 200 mm**	350 mm pass
4.4.8.3	5.8.1	**Strength of side and end** components	**Static load test of side slats** (bending **test)**	**P=250 N, t=30 s**	pass
	5.8.2		**Strength of sides or side slats (impact test)**	10 x each slat	pass
	5.8.3		**Strength of corners (impact test)**	**5 x from outside, 5 x from inside, each corner**	pass
	5.8.4		Strength **of the mesh and other flexible materials**	**P=250 N, t=30 s**	not applicable
4.4.8.4	5.9.1	Strength **of frame and** fastening	Vertical static load test	P=300 N, n=10	pass
	5.9.2		Durability test	**Q=20 kg, P=100 N n=2000 cycles**	pass
4.4.9	5.6	Cot rim		---	not applicable
4.5	5.12	Final stability		**Q=10 kg, P=30 N**	pass
4.6	---	Mattress size		---	not applicable
5	---	Packaging		acc. norm	pass
6	---	Instruction for use		acc. norm	pass
7	---	Marking		acc. norm	not tested

*/ - force needed to remove the rungs - approx. 62 N

Optional drawer – weight – 8.7 kg – usable load 15 kg

Test operator

.....

/M.Sc.(Eng.). Piotr Błaszczak/

END OF TEST REPORT